

Model: AC5 CROSS ESPIGA NATURAL

Codes: 100226686

Group: G-219

Format: 29,34X118,4X0,8



COMPOSITION







	Size	Material	Type of material
Layer 1	0.06	Overlay	
Layer 2	0.1	Decorative paper	
Layer 3	7.7	HDF Extreme	
Layer 4	0.14	Backside	Kraft counterbalance

ADDITIONAL NOTES

High resistance to water and moisture as long as the instructions for installation of this product for these cases are followed.

FEATURES

-  Imitates the surface of wood
-  Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.
-  25 year warranty for domestic use valid for laminate floors that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with EN 13329.
-  Floor capable of dissipating excess electrical charges and distribute them over its entire surface
-  Safety and joint durability are the main features of this easy installation system that guarantees the elimination of gaps between boards throughout the floor's lifetime. The pressure exerted between boards reinforces the union and prevents it from being carried out incorrectly.
-  33. Intensive commercial
-  Suitable for bathroom and kitchen floors for residential use, provided that the product's installation instructions are always followed.
-  Gloss-free
-  5 year warranty for commercial use valid for laminate floors that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with EN 13329.
-  Is suitable for installing on water radiant heating
-  PanEuropean Forest Certification that guarantees to consumers the origin of the products from sustainably managed forests
-  23. Intensive residential
-  ACS Abrasion-resistance level as per Standard UNE-EN 13329

DIMENSIONAL FEATURES

Item thickness	≤0.50 del valor nominal MM	UNE EN 13329:2016*
Length of face	≤1500: Δl≤0.5 mm	UNE EN 13329:2016*
Uv light fastness	≥Grado 4 en escala de grises	EN 20105-A02*



LABORATORY TESTS

Resistance to abrasion	AC5	UNE EN 13329:2000*
Impact resistance	CLASE IC3	EN13329 tabla 2*
Resistance to staining	Grupo 1-2≥5/Grupo 3≥4	EN-438-2 / EN 13329*
Swelling in thickness	≤10%	EN 13329*
Formaldehyde emissions	E1	EN 717-2*
Slip resistance (pendulum-wet)	CL 1 (27)	UNE 41901*
Tensile strength of joints	F≥1 kN/ml	EN 13329*
Fire resistance	Bfl-s1	EN 13501*
Evaluation of propensity to accumulation of electrostatic charges	≤2 kV	EN 1815*
Residual footprint	≤5 MM	EN ISO 24343-1*
Acoustic insulation	ΔLw=17 dB	ISO 10140*
Slip resistance (dcof)	0.60	ANSI A137.1*
Density of the board	940 ±5 KG/M3	UNE EN 323*
Slip resistance (pendulum-dry)	CL 3 (52)	UNE 41902*

PACKING

Sales units per box	2.084314 M2/BOX
Sales units per pallet	106.299991 M2/PAL
Sales units per unit	0.347386 M2/PIECE
Sale unit	M2
Base unit	ST
Sales units per square meter	1 M2
Net weight	7.907639 KG/M2
Gross weight	8.362465 KG/M2

SPECIAL PIECES

SAP	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net Weight	Gross weight
100230248	IGUALACION CROSS ESPIGA NATURAL 4X270X1	G-155	20 PIECES/BOX	1000 PIECES/PAL	9.26 PIECES/M2	-	-	0.7 KG/PIECES	0.72 KG/PIECES
100231459	MAMPERLAN AC5 CROSS ESPIGA NATURAL 7X120	G-163	2 PIECES/BOX	200 PIECES/PAL	11.9 PIECES/M2	-	-	1.58 KG/PIECES	1.64 KG/PIECES
100230273	TRANSICION CROSS ESPIGA NATURAL 4X270X1	G-155	20 PIECES/BOX	1000 PIECES/PAL	9.26 PIECES/M2	-	-	0.7 KG/PIECES	0.72 KG/PIECES
100230274	ZOCALO CROSS ESPIGA NATURAL 8X220X1,5	G-107	14 PIECES/BOX	560 PIECES/PAL	5.68 PIECES/M2	-	-	1.8 KG/PIECES	1.86 KG/PIECES

