Model: LUTIER 1L GREY Codes: 100272991 Group: G-235 Format: 18X220X1,4

## L'ANTIC COLONIAL



| COMPOSITION |         |             |                    |                  |  |  |  |  |
|-------------|---------|-------------|--------------------|------------------|--|--|--|--|
|             |         | Size        | Material           | Type of material |  |  |  |  |
|             | Layer 1 | 0.060-0.070 | Varnish            | APRESTO MATTE    |  |  |  |  |
|             | Layer 2 | 2.5         | Hardwood Layer     | Ash wood         |  |  |  |  |
|             | Layer 3 | 9           | Intermediate Layer | PINE             |  |  |  |  |
|             | Layer 4 | 2.5         | Backside           | PINE             |  |  |  |  |
|             |         |             |                    |                  |  |  |  |  |
| TOLERANCES  |         |             |                    |                  |  |  |  |  |

|                                | I O EEI WII I OEEO   |                       |  |  |  |  |  |
|--------------------------------|----------------------|-----------------------|--|--|--|--|--|
| Squareness of the item         | 0.2% of width.       |                       |  |  |  |  |  |
| Curvature                      | 0.1% of length.      |                       |  |  |  |  |  |
| LABORATORY TESTS               |                      |                       |  |  |  |  |  |
| Thermal conductivity           | 0.14 W/M*ºK W/M*K    | UNE-EN 12667:2002**   |  |  |  |  |  |
| Heat resistance                | 0.103 M2*ºK/W M2*K/W | UNE-EN 12667:2002**   |  |  |  |  |  |
| Formaldehyde emissions         | 0.011 ±0.001 mg/m3   | EN-717/1:2006**       |  |  |  |  |  |
| Flammability                   | Dfl-S1               | UNE EN 13501-1:2007** |  |  |  |  |  |
| Bulk density                   | min 500Kg/m3         | UNE-EN 323:1994**     |  |  |  |  |  |
| Slip resistance (pendulum-wet) | CL 1 (36)            | UNE 41901*            |  |  |  |  |  |
| Slip resistance (pendulum-dry) | 0.51                 | ANSI A137.1*          |  |  |  |  |  |
|                                |                      |                       |  |  |  |  |  |



It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A.U., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use aggressive cleaning agents, such as acids, or metallic or sharp elements. In public places this material must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.U.

## L'ANTIC COLONIAL

|                                   | FEATURES   |              |   |  |  |  |  |  |
|-----------------------------------|--|--------------|---|--|--|--|--|--|
| Ð                                 | It is one of the easiest to install and safest systems in the market. We just need to adjust the board to be installed longitudinally to the one already placed, by applying a soft pressure without the need for any type of tool. Both pieces will fit and will be secured thanks to the safety tab. It is just as simple to take apart, which makes for a quick disassembly |              | Ø | Applying a color oil or varnish on the wood surface in order to get different color ranges.  |  |  |  |  |
| A                                 | L'ANTIC COLONIAL's varnishing, in two finishes, APRESTO (gloss) and APRESTO<br>MATE (matte), provides a unique surface quality that satisfies the most<br>demanding requirements. Advantages: It achieves the highest cleanliness<br>because, since the pores are sealed, dirt and dust remain on the surface and can<br>be easily cleaned.                                    |              |   | Quality product made with selected raw materials, guaranteeing its full residential use for 30 years as provided by L' Antic Colonial.   |  |  |  |  |
| õ                                 | Is suitable for installing on water radiant heating  |              |   | Format where only one board has been used to finish the entire base surface  |  |  |  |  |
| $\bigcirc$                        | Material with some knots on its surface that can have different sizes depending<br>on the type of wood. These, along with any cracks that may appear, are covered<br>with putty.   |              |   | Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.   |  |  |  |  |
| Ś                                 | It is necessary to apply adhesive for installing it.   |              |   | Made from ash wood.  |  |  |  |  |
|                                   | There are considerable color changes between pieces.   |              |   | Material from a European country.  |  |  |  |  |
|                                   | Independent (non-governmental) certificate that guarantees consumers that forest products come from rationally exploited forests   |              |   | Structure formed by an upper layer that shows the noble aspect of the material,<br>an intermediate layer of wood of different typology, depending on the collection,<br>or HDF board that compensates the tensions between the different parts and a<br>lower plywood that provides dimensional stability. |  |  |  |  |
| 2.5 1                             | 2.5 mm   |              |   | Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.   |  |  |  |  |
| Ś                                 | It is necessary to apply adhesive for installing it.   |              |   |  |  |  |  |  |
| PACKING                           |  |              |   |  |  |  |  |  |
| Sales u                           | inits per box  | 2.772 M2/BOX |   |  |  |  |  |  |
| Sales u                           | Sales units per pallet 110.88 M2/PAL   |              |   |  |  |  |  |  |
| Sales units per square meter 1 M2 |  |              |   |  |  |  |  |  |
| Sale unit M2                      |  |              |   |  |  |  |  |  |

| Base unit      |                                    | ST    |                |                 |                |     |            |                |                |  |
|----------------|------------------------------------|-------|----------------|-----------------|----------------|-----|------------|----------------|----------------|--|
| Net weight     |                                    |       | 8.621212 KG/M2 |                 |                |     |            |                |                |  |
| Gross weight   |                                    |       | 9.060606 KG/M2 |                 |                |     |            |                |                |  |
| SPECIAL PIECES |                                    |       |                |                 |                |     |            |                |                |  |
| SAP            | Description                        | Group | Boxes          | Pallet          | Units          | SKU | Basic Unit | Net Weight     | Gross weight   |  |
| 100272965      | IGUALACION LUTIER GREY 4,5X270X1,3 | G-161 | 10 PIECES/BOX  | 1000 PIECES/PAL | 8.23 PIECES/M2 | -   | -          | 1 KG/PIECES    | 1.02 KG/PIECES |  |
| 100272994      | MAMPERLAN LUTIER 1L GREY 7X120X3   | G-163 | 2 PIECES/BOX   | 200 PIECES/PAL  | 11.9 PIECES/M2 | -   | -          | 1.58 KG/PIECES | 1.64 KG/PIECES |  |
| 100272937      | TRANSICION LUTIER GREY 4X270X1,3   | G-161 | 10 PIECES/BOX  | 1000 PIECES/PAL | 9.26 PIECES/M2 | -   | -          | 1 KG/PIECES    | 1.02 KG/PIECES |  |
| 100272955      | ZOCALO LUTIER GREY 8X220X1,4       | G-128 | 12 PIECES/BOX  | 600 PIECES/PAL  | 5.68 PIECES/M2 | -   | -          | 1.33 KG/PIECES | 1.38 KG/PIECES |  |



It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A.U., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use aggressive cleaning agents, such as acids, or metallic or sharp elements. In public places this material must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.U.