L'ANTIC COLONIAL

Model: AC4 ENDLESS 1L BROADWAY

Codes: 100312894 Group: G-210

Format: 24,4X126,1X0,8



COMPOSITION Size Type of material Material Layer 1 0.2 Melamine Aminoplastic thermosetting resins Layer 2 Decorative paper High-density Fiber Board and water-repellent glues Laver 3 HDF Sheets of kraft paper impregnated with phenolic resins Layer 4 Backside

CERTIFICATIONS

CARB: Phase II compliant Carb certification

FEATURES



Boards that have continuity between them, thus achieving the optical effect of much longer formats



Beveled cut on the long sides of the board in order to create a continuity effect





20 year warranty for domestic use valid for laminate floors that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with EN 13329.



Format where only one board has been used to finish the entire base surface



PanEuropean Forest Certification that guarantees to consumers the origin of the products from sustainably managed forests



23. Intensive residential



Abrasion-resistance level as per Standard UNE-EN 13329



Imitates the surface of wood



Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.



5 year warranty for commercial use valid for laminate floors that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with EN 13329.



Is suitable for installing on water radiant heating



Safety and joint durability are the main features of this easy installation system that guarantees the elimination of gaps between boards throughout the floor's lifetime. The pressure exerted between boards reinforces the union and prevents it from being carried out incorrectly.



32. General commercial





It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A.U., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use aggressive cleaning agents, such as acids, or metallic or sharp elements. In public places, this material must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.U.

ACA ENDLESS 11 BROADWAY

L'ANTIC COLONIAL

DIMENSIONAL FEATURES						
Item thickness	≤0.50 mm	EN 13329*				
Length of face	≤0.50 mm	EN 13329*				
Width of face	≤0.20 mm	EN 13329*				
Squareness of the item (q)	≤0.20 mm	EN 13329*				
Straightness of face	≤0.30 mm/m	EN 13329*				
Flatness of item (f)	fw,Cóncavo≤0.50% fw,Convexo≤1%/fl,Cóncavo≤0.15% fl,Convexo≤0.20%	EN 13329*				
Joint between items	≤0.20 mm	EN 13329*				
Difference in height among items	≤0.15 mm	EN 13329*				
Dimensional variations related to changes in relative moisture	≤0.90 mm	EN 13329*				
Uv light fastness	≥4	EN 438-2,16*				

LABORATORY TESTS							
Resistance to abrasion	AC4	UNE EN 13329:2000*					
Impact resistance	IC2	EN 13329*					
Resistance to staining	Grado 5 (G 1 y 2) y Grado 4 (G 3)	EN 438*					
Resistance to cigarette burns	4	EN 438*					
Furniture leg effect	No damage	EN 424*					
Castor chair effect	No damage	EN 425*					
Swelling in thickness	≤18%	UNE-EN 13329:2000*					
Dimensional stability	0.03%	EN 434:1994*					
Formaldehyde emissions	E1	EN 717*					
Slip resistance (pendulum-wet)	CL 1 (33)	UNE 41901*					
Tensile strength of joints	F≥1 kN/ml	EN 13329*					
Fire resistance	Cfl-s1	EN 13501*					
Evaluation of propensity to accumulation of electrostatic charges	1.2 kV	ISO 1815*					
Heat resistance	R=0.057 m2 K/W	ISO 8302*					
Curvature	0.06 mm						
Swelling in thickness	≤18%	ASTM D 1037*					
Slip resistance (dcof)	0.58	ANSI A137.1*					
Critical radiant flux	Cfl	EN ISO 9239-1*					
Smoke density (burning)	s1	EN 13501-1*					
Density of the board	925 ±5 KG/M3	UNE EN 323*					
Slip resistance (pendulum-dry)	CL 3 (52)	UNE 41902*					

PACKING			
Sales units per box	2.461472 M2/BOX		
Sales units per pallet	103.381822 M2/PAL		
Sales units per unit	0.307684 M2/PIECE		
Sale unit	M2		
Base unit	ST		
Sales units per square meter	1 M2		
Net weight	7.572705 KG/M2		
Gross weight	7.78396 KG/M2		

SPECIAL PIECES									
SAP	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net Weight	Gross weight
100153848	IGUALACION ENDLESS 1L BROADWAY 4X270X1	G-155	20 PIECES/BOX	1000 PIECES/PAL	9.26 PIECES/M2	-	-	0.77 KG/PIECES	0.8 KG/PIECES
100176686	MAMPERLAN AC4 ENDLESS 1L BROADWAY7X120X3	G-163	2 PIECES/BOX	200 PIECES/PAL	11.9 PIECES/M2	-	-	1.58 KG/PIECES	1.64 KG/PIECES
100153885	TRANSICION ENDLESS 1L BROADWAY 4X270X1	G-155	20 PIECES/BOX	1000 PIECES/PAL	9.26 PIECES/M2	-	-	0.77 KG/PIECES	0.77 KG/PIECES
100153892	ZOCALO ENDLESS 1L BROADWAY 8X220X1,5	G-107	14 PIECES/BOX	560 PIECES/PAL	5.68 PIECES/M2	-	-	1.8 KG/PIECES	1.86 KG/PIECES





It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A.U., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use aggressive cleaning agents, such as acids, or metallic or sharp elements. In public places, this material must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.U.

01/03/2023