















Model: AC5 CROSS CHEVRON SILVER
Codes: 100313973
Group: G-219
Format: 29,34X118,4X0,8



COMPOSITION				
		Size	Material	Type of material
	Layer 1	0.06	Overlay	
	Layer 2	0.1	Decorative paper	
	Layer 3	7.7	HDF Extreme	
	Layer 4	0.14	Backside	Kraft counterbalance

ADDITIONAL NOTES	
High resistance to water and moisture as long as the instructions for installation of this product for these cases are followed.	

FEATURES	
 Imitates the surface of wood	 Gloss-free
 Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.	 25 25 year warranty for domestic use valid for laminate floors that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with EN 13329.
 5 5 year warranty for commercial use valid for laminate floors that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with EN 13329.	 Is suitable for installing on water radiant heating
 Floor capable of dissipating excess electrical charges and distribute them over its entire surface	 PEFC PanEuropean Forest Certification that guarantees to consumers the origin of the products from sustainably managed forests
 Safety and joint durability are the main features of this easy installation system that guarantees the elimination of gaps between boards throughout the floor's lifetime. The pressure exerted between boards reinforces the union and prevents it from being carried out incorrectly.	 23. Intensive residential
 33. Intensive commercial	 ACS Abrasion-resistance level as per Standard UNE-EN 13329
 Suitable for bathroom and kitchen floors for residential use, provided that the product's installation instructions are always followed.	

DIMENSIONAL FEATURES		
Item thickness	≤0.50 del valor nominal MM	UNE EN 13329:2016*
Length of face	≤1500: Δl≤0.5 mm	UNE EN 13329:2016*
Uv light fastness	≥Grado 4 en escala de grises	EN 20105-A02*



LABORATORY TESTS		
Resistance to abrasion	AC5	UNE EN 13329:2000*
Impact resistance	CLASE IC3	EN13329 tabla 2*
Resistance to staining	Grupo 1-2≥5/Grupo 3≥4	EN-438-2 / EN 13329*
Swelling in thickness	≤10%	EN 13329*
Formaldehyde emissions	E1	EN 717-2*
Slip resistance (pendulum-wet)	CL 1 (27)	UNE 41901*
Tensile strength of joints	F≥1 kN/ml	EN 13329*
Fire resistance	Bfl-s1	EN 13501*
Evaluation of propensity to accumulation of electrostatic charges	≤2 kV	EN 1815*
Residual footprint	≤5 MM	EN ISO 24343-1*
Acoustic insulation	ΔLw=17 dB	ISO 10140*
Slip resistance (dcof)	0.60	ANSI A137.1*
Density of the board	940 ±5 KG/M3	UNE EN 323*
Slip resistance (pendulum-dry)	CL 3 (52)	UNE 41902*

PACKING		
Sales units per box	2.084314 M2/BOX	
Sales units per pallet	106.299991 M2/PAL	
Sales units per unit	0.347386 M2/PIECE	
Sale unit	M2	
Base unit	ST	
Sales units per square meter	1 M2	
Net weight	7.890368 KG/M2	
Gross weight	8.345194 KG/M2	

SPECIAL PIECES									
SAP	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net Weight	Gross weight
100313974	IGUALACION CROSS CHEVRON SILVER 4X270X1	G-155	20 PIECES/BOX	1000 PIECES/PAL	9.26 PIECES/M2	-	-	0.7 KG/PIECES	0.72 KG/PIECES
100313981	MAMPERLAN AC5 CROSS CHEVRON SILVER 7X120	G-163	2 PIECES/BOX	200 PIECES/PAL	11.9 PIECES/M2	-	-	1.58 KG/PIECES	1.64 KG/PIECES
100313990	TRANSICION CROSS CHEVRON SILVER 4X270X1	G-155	20 PIECES/BOX	1000 PIECES/PAL	9.26 PIECES/M2	-	-	0.7 KG/PIECES	0.72 KG/PIECES
100313991	ZOCALO CROSS CHEVRON SILVER 8X220X1,5	G-107	14 PIECES/BOX	560 PIECES/PAL	5.68 PIECES/M2	-	-	1.8 KG/PIECES	1.86 KG/PIECES

